

[Czech]: R-PIW18-XL2 Cordless RawlWrench 18V 1000Nm, set

[Czech]: The 18V impact wrench with a torque of 1000 Nm and a 1/2" square tool holder allows for quick application of concrete screws



Certifikáty



Informace o produktu

Vlastnosti a výhody

- [Czech]: 1/2" square tool holder for stable mounting of impact sockets
- [Czech]: Powerful brushless motor ensures high efficiency of the mechanism and increases the life time of the power tool
- [Czech]: The metal gear housing facilitates cooling and increases power tool life-time
- [Czech]: LED illuminates the work place to increase user comfort and safety
- [Czech]: Rubberised, profiled handle increases grip and user ergonomics
- [Czech]: Powerful impact gear generating up to 1000 Nm allows the power tool with other cases for easy transport to be used for the most demanding fixings applications

Použití

- [Czech]: Installation of R-LX screws diameter 8mm-14mm
- [Czech]: Timber constructions: Screwing screws up to 24 mm
- [Czech]: Metal constructions: assembly of metric screws (up to M24)

Související výrobky

- R-LX-HF-ZF univerzální šroub do betonu s vysoce odolnou povrchovou úpravou Zinc Flake s šestihrannou hlavou s integrovanou podložkou

Podkladový materiál

- Beton
- Železobeton
- Nerezová ocel
- Stavební dřevo

Sada obsahuje

- [Czech]: R-IW-1801B Impact wrench 18V, 1000Nm
- [Czech]: 2 x R-BAT-185001 Battery 18V 5.0Ah
- [Czech]: R-CHR-186501 Charger 18V 6.5A
- [Czech]: R-RC-4414 RawlCase



Logistické údaje

Index	Napětí akumu- látoru	Kapacita akumu- látoru	[Czech]: Number of batte- ries inclu- ded	[Czech]: Charging time	Max.krou- tí cí mo- ment	[Czech]: Tool hol- der	[Czech]: Rotatio- nal speed	Frekven- ce příkle- pu	[Czech]: Maximum bolt size	Hmotnost jednotko- vého ba- lení	Hmotnost hromad- ného ba- lení	EAN
	[V]	[Ah]	[ks]	[min]	[Nm]		[ot./min.]	□	kg	kg		
R-PIW18-XL2	18	5,0	2	50	1000	1/2"	0-1900	0-2800	M24	6.71	6.71	59066754 73734