

[Czech]: R-PDD18-55-M2 Cordless Rawldriver 55NM, 18V

[Czech]: The 18V drill driver allows you to use a high torque of 55 NM to drive screws depending on the hardness of the material.



Informace o produktu

Vlastnosti a výhody

- [Czech]: Powerful brushless motor ensures high efficiency of the mechanism and increases the life time of the power tool
- [Czech]: Rubberised, profiled handle increases grip and user ergonomics
- [Czech]: 16 + 1 positions of the clutch allows optimal selection of torque for driving of bolts and screws of different sizes depending on the type of substrate
- [Czech]: The single-sleeve 13 mm drill chuck makes it easy to install all accessories
- [Czech]: Planetary gear parts are made of high quality steel to increase the tool life-time
- [Czech]: Compact design and lightweight construction reduces fatigue during long-term use

Použití

- [Czech]: Timber constructions: tightening screws up to 6 mm
- [Czech]: Metal constructions: assembly of metric screws (up to M6)
- [Czech]: Frame pins and others up to 14 mm (e.g. FF1, 4ALL)

Související výrobky

- [Czech]: R-PTK Construction screw with wafer head and partial thread
- R-PVS Vrutky pro dřevěné konstrukce
- 4ALL Univerzální hmoždinka se šroubem

Podkladový materiál

- Kovové plechy a profily
- Nerezová ocel
- [Czech]: Plastics
- [Czech]: Decking board
- Dřevo

Sada obsahuje

- [Czech]: R-PDD18-55 Rawl-Driver
- [Czech]: 2 x R-BAT-182001 Battery Li-Ion 18V, 2,0 Ah
- [Czech]: R-CHR-181501 Charger 18V 1.5A
- [Czech]: R-RC-4414 RawlCase system box

Logistické údaje

Index	Napětí akumulatoru	Kapacita akumulatoru	[Czech]: Number of batteries included	[Czech]: Charging time	Max. krouticí moment	[Czech]: Number of clutch settings	[Czech]: Chuck	[Czech]: Rotational speed 1st gear	[Czech]: Rotational speed 2nd gear	[Czech]: Maximum drilling diameter in wood	[Czech]: Maximum drilling diameter in metal	[Czech]: Tool weight without battery	[Czech]: Tool weight with 2.0 Ah battery	Hmotnost jednotkového balení	Hmotnost hromadného balení	EAN
	[V]	[Ah]	[ks]	[min]	[Nm]		[mm]	[ot./min.]	[ot./min.]	[mm]	[mm]	[kg]	[kg]	kg	kg	
R-PDD18-55-M2	18	2,0	2	60	55	16 + 1	2 - 13	0 - 500	0 - 1800	ø 36	ø 13	1,1	1,5	4,37	4,37	590667 55061 97