

R-RBP Rawlbolt® - Bolt Projecting for use in hollow core slab and ceramic substrates

World's most popular all-purpose expanding shield anchor - bolt projecting version



Product information

Features and benefits

- RAWLBOLT® - first ever mechanical anchor in the world, forerunner of all of the later mechanical anchors
- For use in cracked and non-cracked concrete (ETA option 1), hollow-core slabs, flooring blocks and ceramics
- Three-pieces expanding sleeve of maximum expansion provides optimal load and safety of use in any substrate
- Wide range of diameters (M6 to M20)

Applications

- Roller shutter doors
- Fire doors
- Steelwork
- Security grills
- Heavy machinery
- Pipework/duct work support

Base materials

Approved for use in:


- Solid clay brick $\geq 20\text{MPa}$
- Hollow Lightweight Concrete Block LAC 5 $\geq 5\text{MPa}$
- Hollow Sand-lime Brick $\geq 15\text{MPa}$
- Concrete hollow floor block (eg. Teriva)
- Hollow-core Slab C20/25
- Hollow-core Slab C30/37-C50/60

Installation guide




1. Drill a hole of required diameter and depth
2. Remove nut and washer and insert anchor into hole. Tap home with hammer until flush with surface
3. Position fixture over the projecting bolt
4. Add washer and nut and tighten to recommended torque

Product information



Size	Product Code	Anchor			Fixture	
		Diameter	External diameter	Length	Max. thickness	Hole diameter
		d [mm]	d _{nom} [mm]	L [mm]	t _{fix} [mm]	d _f [mm]
M6	R-RBP-M06/10W	6	12	65	10	6,5
	R-RBP-M06/25W	6	12	80	25	6,5
	R-RBP-M06/60W	6	12	115	60	6,5
M8	R-RBP-M08/10W	8	14	75	10	9
	R-RBP-M08/25W	8	14	90	25	9
	R-RBP-M08/60W	8	14	125	60	9
M10	R-RBP-M10/15W	10	16	90	15	11
	R-RBP-M10/30W	10	16	105	30	11
	R-RBP-M10/60W	10	16	135	60	11
M12	R-RBP-M12/15W	12	20	110	15	13
	R-RBP-M12/30W	12	20	125	30	13
	R-RBP-M12/75W	12	20	170	75	13
M16	R-RBP-M16/15W	16	25	150	15	17
	R-RBP-M16/35W	16	25	170	35	17
	R-RBP-M16/75W	16	25	210	75	17
M20	R-RBP-M20/15W	20	32	170	15	22
	R-RBP-M20/30W	20	32	185	30	22
	R-RBP-M20/100W	20	32	255	100	22

Installation data



Size	M6	M8	M10	M12	M16	M20		
Thread diameter	d	[mm]	6	8	10	12	16	20
Hole diameter in substrate	d _o	[mm]	12	14	16	20	25	32
Min. installation depth	h _{nom}	[mm]	45	50	60	80	120	135
Min. hole depth in substrate	h _o	[mm]	50	55	65	85	125	140
Wrench size	Sw	[mm]	10	13	17	19	24	30
SOLID SUBSTRATES								
Installation torque	T _{inst}	[Nm]	6.5	15	27	50	120	230
Min. substrate thickness	h _{min}	[mm]	100	100	100	100	142	172
Min. spacing	s _{min}	[mm]	35	40	50	60	95	115
Min. edge distance	c _{min}	[mm]	53	60	75	90	143	173

Installation data

Size			M6	M8	M10	M12	M16	M20
CERAMIC AND HOLLOW SUBSTRATES								
Installation torque	T_{inst}	[Nm]	3	5	8	10	15	20
Min. spacing	s_{min}	[mm]	100	100	100	100	100	115
Min. edge distance	c_{min}	[mm]	100	100	100	100	143	173

Mechanical properties

Size			M6	M8	M10	M12	M16	M20
Nominal ultimate tensile strength - tension	f_{uk}	[N/mm ²]	500	500	500	500	500	500
Nominal yield strength - tension	f_{yk}	[N/mm ²]	400	400	400	400	400	400
Cross sectional area - tension	A_s	[mm ²]	20.1	36.6	58	84.3	157	245
Elastic section modulus	W_{el}	[mm ³]	21.21	50.27	98.17	169.65	402.12	785.4
Characteristic bending resistance	$M_{Rk,s}^0$	[Nm]	12.72	30.16	58.9	101.79	241.27	471.24
Design bending resistance	M	[Nm]	10.18	24.13	47.12	81.43	193.02	376.99

Basic performance data

Performance data for single anchor without influence of edge distance and spacing - ETAG 001

Size			M6	M8	M10	M12	M16	M20
CHARACTERISTIC LOAD								
TENSION LOAD N_{rk}								
Hollow core slab min. C20/25								
Wall thickness	Material class							
23	C30/37	[kN]	4.00	4.50	-	-	-	-
	C35/45	[kN]	2.00	4.50	-	-	-	-
	C45/55	[kN]	2.00	4.50	-	-	-	-
	C50/60	[kN]	2.00	4.50	-	-	-	-
35	C30/37	[kN]	6.50	11.00	16.00	-	-	-
	C35/45	[kN]	7.00	12.00	17.00	-	-	-
	C45/55	[kN]	8.00	14.00	19.00	-	-	-
	C50/60	[kN]	8.50	15.00	20.00	-	-	-
40	C30/37	[kN]	7.00	16.00	19.00	24.00	-	-
	C35/45	[kN]	8.00	18.00	20.00	28.00	-	-
	C45/55	[kN]	8.50	20.00	22.00	30.00	-	-
	C50/60	[kN]	9.50	22.00	24.00	32.00	-	-
50	C20/25	[kN]	8.00	8.50	8.50	8.50	8.50	8.50
Beam-and-block floor (eg.Terriva 4.0/2), min. 25mm wall thickness		[kN]	1.20	2.00	-	-	-	-
Lightweight concrete LAC class 5		[kN]	5.50	5.50	5.50	5.50	-	-
Solid clay brick class 20		[kN]	6.00	6.00	6.00	6.00	-	-
Silicate hollow block class 15		[kN]	1.50	-	-	-	-	-
SHEAR LOAD V_{rk}								
Hollow core slab min. C20/25								
Wall thickness	Material class							
23	C30/37	[kN]	4.00	4.50	-	-	-	-
	C35/45	[kN]	2.00	4.50	-	-	-	-
	C45/55	[kN]	2.00	4.50	-	-	-	-
	C50/60	[kN]	2.00	4.50	-	-	-	-
35	C30/37	[kN]	5.00	9.00	14.00	-	-	-
	C35/45	[kN]	5.00	9.00	14.00	-	-	-
	C45/55	[kN]	5.00	9.00	14.00	-	-	-
	C50/60	[kN]	5.00	9.00	14.00	-	-	-
40	C30/37	[kN]	5.00	9.00	14.00	20.00	-	-
	C35/45	[kN]	5.00	9.00	14.00	20.00	-	-
	C45/55	[kN]	5.00	9.00	14.00	20.00	-	-
	C50/60	[kN]	5.00	9.00	14.00	20.00	-	-
50	C20/25	[kN]	5.00	8.50	8.50	8.50	8.50	8.50
Beam-and-block floor (eg.Terriva 4.0/2), min. 25mm wall thickness		[kN]	1.20	2.00	-	-	-	-
Lightweight concrete LAC class 5		[kN]	5.00	5.50	5.50	5.50	-	-
Solid clay brick class 20		[kN]	5.00	6.00	6.00	6.00	-	-
Silicate hollow block class 15		[kN]	1.50	-	-	-	-	-

Basic performance data

Size			M6	M8	M10	M12	M16	M20
DESIGN LOAD								
TENSION LOAD N_{rd}								
Hollow core slab min. C20/25								
Wall thickness	Material class							
23	C30/37	[kN]	2.20	2.50	-	-	-	-
	C35/45	[kN]	1.10	2.50	-	-	-	-
	C45/55	[kN]	1.10	2.50	-	-	-	-
	C50/60	[kN]	1.10	2.50	-	-	-	-
35	C30/37	[kN]	3.60	6.10	8.90	-	-	-
	C35/45	[kN]	3.90	6.70	9.40	-	-	-
	C45/55	[kN]	4.40	7.80	10.60	-	-	-
	C50/60	[kN]	4.70	8.30	11.10	-	-	-
40	C30/37	[kN]	3.90	8.90	10.60	13.30	-	-
	C35/45	[kN]	4.40	10.00	11.10	15.60	-	-
	C45/55	[kN]	4.70	11.10	12.20	16.70	-	-
	C50/60	[kN]	5.30	12.20	13.30	17.80	-	-
50	C20/25	[kN]	4.40	4.70	4.70	4.70	4.70	4.70
Beam-and-block floor (eg.Terriva 4.0/2), min. 25mm wall thickness		[kN]	0.70	1.10	-	-	-	-
Lightweight concrete LAC class 5		[kN]	2.00	2.20	2.20	2.20	-	-
[English]: Cegła ceramiczna pełna 20MPa		[kN]	2.00	2.40	2.40	2.40	-	-
Silicate hollow block class 15		[kN]	0.60	-	-	-	-	-
SHEAR LOAD V_{rd}								
Hollow core slab min. C20/25								
Wall thickness	Material class							
23	C30/37	[kN]	3.20	3.60	-	-	-	-
	C35/45	[kN]	1.60	3.60	-	-	-	-
	C45/55	[kN]	1.60	3.60	-	-	-	-
	C50/60	[kN]	1.60	3.60	-	-	-	-
35	C30/37	[kN]	4.00	7.20	11.20	-	-	-
	C35/45	[kN]	4.00	7.20	11.20	-	-	-
	C45/55	[kN]	4.00	7.20	11.20	-	-	-
	C50/60	[kN]	4.00	7.20	11.20	-	-	-
40	C30/37	[kN]	4.00	7.20	11.20	16.00	-	-
	C35/45	[kN]	4.00	7.20	11.20	16.00	-	-
	C45/55	[kN]	4.00	7.20	11.20	16.00	-	-
	C50/60	[kN]	4.00	7.20	11.20	16.00	-	-
50	C20/25	[kN]	4.00	6.80	6.80	6.80	6.80	6.80
Beam-and-block floor (eg.Terriva 4.0/2), min. 25mm wall thickness		[kN]	1.00	1.60	-	-	-	-
Lightweight concrete LAC class 5		[kN]	4.00	4.40	4.40	4.40	-	-
[English]: Cegła ceramiczna pełna 20MPa		[kN]	4.00	4.80	4.80	4.80	-	-
Silicate hollow block class 15		[kN]	1.20	-	-	-	-	-

Basic performance data

Size			M6	M8	M10	M12	M16	M20
RECOMMENDED LOAD								
TENSION LOAD N_{rec}								
Hollow core slab min. C20/25								
Wall thickness	Material class							
23	C30/37	[kN]	1.60	1.80	-	-	-	-
	C35/45	[kN]	0.80	1.80	-	-	-	-
	C45/55	[kN]	1.60	1.80	-	-	-	-
	C50/60	[kN]	0.80	1.80	-	-	-	-
35	C30/37	[kN]	2.60	4.40	6.30	-	-	-
	C35/45	[kN]	2.80	4.80	6.70	-	-	-
	C45/55	[kN]	3.20	5.60	7.50	-	-	-
	C50/60	[kN]	3.40	6.00	7.90	-	-	-
40	C30/37	[kN]	2.80	6.30	7.50	9.50	-	-
	C35/45	[kN]	3.20	7.10	7.90	11.10	-	-
	C45/55	[kN]	3.40	7.90	8.70	11.90	-	-
	C50/60	[kN]	3.80	8.70	9.50	12.70	-	-
50	C20/25	[kN]	3.20	3.40	3.40	3.40	3.40	3.40
Beam-and-block floor (eg.Terriva 4.0/2), min. 25mm wall thickness		[kN]	0.50	0.80	-	-	-	-
Lightweight concrete LAC class 5		[kN]	1.40	1.60	1.60	1.60	-	-
[English]: Cegła ceramiczna pełna 20MPa		[kN]	1.40	1.70	1.70	1.70	-	-
Silicate hollow block class 15		[kN]	0.40	-	-	-	-	-
SHEAR LOAD V_{rec}								
Hollow core slab min. C20/25								
Wall thickness	Material class							
23	C30/37	[kN]	2.30	2.60	-	-	-	-
	C35/45	[kN]	1.10	2.60	-	-	-	-
	C45/55	[kN]	1.10	2.60	-	-	-	-
	C50/60	[kN]	1.10	2.60	-	-	-	-
35	C30/37	[kN]	2.90	5.10	8.00	-	-	-
	C35/45	[kN]	2.90	5.10	8.00	-	-	-
	C45/55	[kN]	2.90	5.10	8.00	-	-	-
	C50/60	[kN]	2.90	5.10	8.00	-	-	-
40	C30/37	[kN]	2.90	5.10	8.00	11.40	-	-
	C35/45	[kN]	2.90	5.10	8.00	11.40	-	-
	C45/55	[kN]	2.90	5.10	8.00	11.40	-	-
	C50/60	[kN]	2.90	5.10	8.00	11.40	-	-
50	C20/25	[kN]	2.90	4.90	4.90	4.90	4.90	4.90
Beam-and-block floor (eg.Terriva 4.0/2), min. 25mm wall thickness		[kN]	0.70	1.10	-	-	-	-
Lightweight concrete LAC class 5		[kN]	2.90	3.10	3.10	3.10	-	-
[English]: Cegła ceramiczna pełna 20MPa		[kN]	2.90	3.40	3.40	3.40	-	-
Silicate hollow block class 15		[kN]	0.90	-	-	-	-	-

Product commercial data

Product Code	Anchor		Quantity [pcs]			Weight [kg]			Bar Codes
	Diameter [mm]	Length [mm]	Box	Outer	Pallet	Box	Outer	Pallet	
R-RBP-M06/10W	6	65	50	400	16000	1.59	12.7	538.8	5906675283593
R-RBP-M06/25W	6	80	50	400	16000	1.73	13.8	582.0	5906675283616
R-RBP-M06/60W	6	115	50	50	8000	2.0	2.0	354.0	5906675283630
R-RBP-M08/10W	8	75	50	400	16000	2.9	22.9	946.8	5906675283654
R-RBP-M08/25W	8	90	50	50	8000	3.1	3.1	528.4	5906675283678
R-RBP-M08/60W	8	125	50	50	8000	3.7	3.7	614.8	5906675283692
R-RBP-M10/15W	10	90	50	50	8000	5.0	5.0	825.2	5906675283715
R-RBP-M10/30W	10	105	50	50	6000	5.3	5.3	666.0	5906675283739
R-RBP-M10/60W	10	135	50	50	8000	6.1	6.1	998.0	5906675283753
R-RBP-M12/15W	12	110	25	25	4000	4.6	4.6	767.2	5906675283760
R-RBP-M12/30W	12	125	25	25	4000	4.9	4.9	818.4	5906675283777
R-RBP-M12/75W	12	170	25	25	3000	5.8	5.8	721.8	5906675283784
R-RBP-M16/15W	16	150	10	10	1600	4.4	4.4	733.5	5906675283791
R-RBP-M16/35W	16	170	10	10	1600	4.7	4.7	773.5	5906675283807
R-RBP-M16/75W	16	210	10	10	1200	5.3	5.3	662.9	5906675283814
R-RBP-M20/15W	20	170	10	10	1200	8.0	8.0	985.1	5906675283821
R-RBP-M20/30W	20	185	10	10	1200	8.3	8.3	1030.4	5906675283838
R-RBP-M20/100W	20	255	10	10	1200	9.9	9.9	1219.2	5906675284781