

R-XPC-300 Express Cement

Express Cement - single component, ready to use repair mortar based on polymers.

Product information



Applications

- Repairing masonry joints and roof tiles
- Repairing chipped edges
- General repair work

Features and benefits

- Repairing mortar is resistant to changing weather conditions (from -20°C to +70°C) and UV radiation.
- Mortar can be applied to slightly wet surfaces.
- Saves time - no need for pre-mixing.
- Mortar is suitable for indoor and outdoor applications.
- Excellent adhesion to common building substrates.

Base materials

Approved for use in:

- Concrete
- Aerated Concrete Block
- Ceramics
- Solid Brick
- Wood
- Plasterboard
- Gypsum Fibreboards
- Masonry

Installation guide



1. The surface, that repair mortar will be applied on should be clean, free of dust, free of old seal and other substances that might weaken the adhesion.
2. Before using the product, it is recommended to perform an adhesion test on the intended substrate.
3. Cut the tip of the applicator to the appropriate diameter.
4. Outflow of the mortar should be regulate by the appropriate pressure on the application gun.
5. Mortar Fix-Pro hardens by the reaction with moisture from the air. For that reason ensure well-ventilated conditions.
6. After completing the application, put the tip on the applicator to protect the mass against hardening.
7. Remove excess of uncured mortar from surfaces, tools, hands using paper towel.
8. Remove cured mass from tools or surfaces mechanically, then wash with water and/or detergent.

Technical Data

Parameter		Value	Methods
Application temperature	-	+5 ÷ +40	
Thermal resistance (upon hardening)	-	-20 ÷ +70	
Density	[g/cm ³]	1.85	
Curing time	[mm/24h]	4	
Open time	-	6	
Skin formation time	-	8	
Cutting	-	papier ścierny gr. 240	
Packaging	-	300 ml cartridge	
R-XPC-300-GREY-PL			
Colour	-	grey	
R-XPC-300-SAND-PL			
Colour	-	sand	

Parameter		Value
Storage temperature	[°C]	+5 ÷ +35
Storage	[month]	18
	-	In originally closed containers, in cool and dry places.

Product commercial data

Product Code	Colour	Quantity [pcs]			Weight [kg]			Bar Codes
		Box	Outer	Pallet	Box	Outer	Pallet	
R-XPC-300-GREY-PL	grey	15	15	1260	8.4	8.4	738.1	5906675467993
R-XPC-300-SAND-PL	sand	15	15	1260	8.4	8.4	738.1	5906675468006