

R-PID18-M2 Cordless Rawlwrench 18V 210NM

Impact driver 18V with a torque of 210 Nm and multi-head holder allows you to work with bits and sockets



Certificate



Product information

Features and benefits

- Multihead tool holder - 1/4" hexagonal shank for bits and 1/2" square for sockets provides broad usability of the power tool
- Electronic adjustable torque range to match power tool parameters for a specific application
- Powerful brushless motor ensures high efficiency of the mechanism and increases the life time of the power tool
- Auto Stop Control ASC, torque cut off mode prevents damage to the material surface during screwing
- Rubberised, profiled handle increases grip and user ergonomics
- Electronic protection stop system engages during jamming to protect the user and th

Applications

- Timber constructions: Screwing screws up to Ø 14 mm
- Metal constructions: Assembly of metric screws (up to M14)
- Installation of R-LX concrete screws up to Ø 8 mm

Corresponding products

- R-PTX Construction screw with countersunk head and partial thread
- R-DSX-A2 Stainless steel decking screws
- RT-IBIT-T T type impact screwdriver bits

Base materials

- Concrete
- Reinforced concrete
- Solid Brick
- High-Density Natural Stone
- Stainless Steel
- Timber

Set includes

- R-ID-1801B Impact wrench
- [English]: 2 x R-BAT-182001 Akumulator Li-Ion 18V, 2,0 Ah
- R-CHR-181501 Charger 18V 1.5A
- R-RC-4414 RawlCase system box



Product commercial data

| Index | Battery voltage | Battery capacity | Number of batteries included | Charging time | Max. torque | Tool holder | Rotational speed | Impact frequency | Maximum bolt size | Box weight | Outer weight | EAN |
|------------|-----------------|------------------|------------------------------|---------------|-------------|-----------------|---------------------|----------------------|-------------------|------------|--------------|----------------|
| | [V] | [Ah] | [pcs] | [min] | [Nm] | | [r/min] | [bpm] | | kg | kg | |
| R-PID18-M2 | 18 | 2,0 | 2 | 60 | 210 | 1/4" HEX / 1/2" | 0-110 / 2600 / 3200 | 0-1200 / 2700 / 3800 | M14 | 4.15 | 4.15 | 59066754 90915 |