

# R-PDD18-P100-XL2 Cordless RawlDriver 18V, set

The 18V drill driver allows you to use a high torque of 100 NM to drive screws depending on the hardness of the material. You can drill holes in the light concrete



## Product information

### Features and benefits

- Powerful brushless motor ensures high efficiency of the mechanism and increases the life time of the power tool
- [English]: Funkcja wiercenia udarowego umożliwia pracę w cegle i lekkim betonie
- Rubberised, profiled handle increases grip and user ergonomics
- 14 + 2 positions of the clutch allows optimal selection of torque for driving of bolts and screws of different sizes depending on the type of substrate
- The single-sleeve 13 mm drill chuck makes it easy to install all accessories
- Planetary gear parts are made of high quality steel to increase the tool life-time
- LED illuminates the work place to increase user comfort and safety

### Applications

- Timber constructions: tightening screws up to 6 mm
- Metal constructions: assembly of metric screws (up to M6)
- Frame pins and others up to 14 mm (e.g. FF1, 4ALL)
- Drilling sheets with a thickness of 2 mm to 10mm

### Corresponding products

- R-PTK Construction screw with wafer head and partial thread
- R-PVS Construction screw with countersunk head and full thread

### Base materials

- Metal Sheet & Profiles
- Solid Brick
- Plastics
- Decking board
- Wood
- Chipboard

### Set includes

- R-PDD18-P100 RawlDriver
- 2 x R-BAT-185001 Battery Li-Ion 18V, 5,0 Ah
- R-CHR-186501 Charger 18V 6,5A
- R-RC-4414 RawlCase system box
- Manual user instructions

## Product commercial data

Index	Battery voltage	Battery capacity	Number of batteries included	Charging time	Max. torque	Number of clutch settings	Chuck	Rotational speed 1st gear	Rotational speed 2nd gear	Maximum drilling diameter in wood	Maximum drilling diameter in metal	Maximum drilling diameter in brick	Tool weight without battery	Tool weight with 5.0 Ah battery	Box weight	Outer weight	EAN
	[V]	[Ah]	[pcs]	[min]	[Nm]		[mm]	[r/min]	[r/min]	[mm]	[mm]	[mm]	[kg]	[kg]	kg	kg	
R-PDD18-P100-XL2	18	5,0	2	50	100	14 + 2	2 - 13	0 - 550	0 - 2100	ø 80	ø 13	ø 16	2,1	2,7	6.18	6.18	59066 755062 27