

# R-PDD18-P100-XL2UK Cordless RawlDriver 100Nm 18V

The 18V drill driver allows you to use a high torque of 100 NM to drive screws depending on the hardness of the material. You can drill holes in the light concrete



### **Product information**

#### Features and benefits

- Powerful brushless motor ensures high efficiency of the mechanism and increases the life time of the power tool
- [English]: Funkcja wiercenia udarowego umożliwia pracę w cegle i lekkim betonie
- Rubberised, profiled handle increases grip and user ergonomics
- 14 + 2 positions of the clutch allows optimal selection of torque for driving of bolts and screws of different sizes depending on the type of substrate
- The single-sleeve 13 mm drill chuck makes it easy to install all accessories
- Planetary gear parts are made of high quality steel to increase the tool life-time
- LED illuminates the work place to increase user comfort and safety

### **Applications**

- Timber constructions: tightening screws up to 6 mm
- Metal constructions: assembly of metric screws (up to M6)
- Frame pins and others up to 14 mm (e.g. FF1, 4ALL)
- Drilling sheets with a thickness of 2 mm to 10mm

## Corresponding products

- R-PTK Construction screw with wafer head and partial thread
- R-PVS Construction screw with countersunk head and full thread

### **Base materials**

- Metal Sheet & Profiles
- Solid Brick
- Plastics
- · Decking board
- Wood
- Chipboard

### Set includes

- R-PDD18-P100 RawlDriver
- 2 x R-BAT-185001 Battery Li-lon 18V, 5,0 Ah
- R-CHR-186501 Charger 18V 6,5A
- R-RC-4414 RawlCase system box
- · Manual user instructions



### Product commercial data

Index	Batte- ry vol- tage	Batte- ry ca- pacity	Num- ber of batte- ries inclu- ded		Max. torque	Num- ber of clutch set- tings	Chuck	Rota- tional speed 1st ge- ar		diame- ter in	Maxi- mum dril- ling diame- ter in metal	mum dril- ling diame- ter in	witho- ut bat-	S O A b	Box weight	Outer weight	EAN
	[v]	0	[pcs]	[min]	[Nm]		[mm]	[r/min]	[r/min]	[mm]	[mm]	[mm]	[kg]	[kg]	kg	kg	
R-PDD18-P100-XL2UK	18	5,0	2	50	100	14 + 2	2 - 13	0 - 550	0 - 2100	ø 80	ø 13	ø 16	2,1	2,7	6.18	6.18	59066 755105 90