

MN-65-8 Circular saw for wood

Circular saws with carbide teeth intended for cutting soft and hard wood



Features & benefits

- Carbides cemented in the saw increase the service life of the disc
- Disc has special compensating grooves for better heat dissipation so that the discs do not heat up and retain constant cutting parameters
- Properly chosen tile geometry allows you to obtain optimal processing quality of the material while transverse cutting
- Saw disc hardness 38-40 HRC increases the service life of the product
- Reducing rings of the inner bore allow you to work with most circular saws available on the market

Applications

- For transverse cutting of soft and hard wood
- Intended for use with circular saw

Equipment

- Reducing ring of blade mounting

Users

- DIY enthusiasts
- Carpenters
- Joiners
- Roofers
- Gardeners

Corresponding products

- MN-91-144 Circular saw 18V, 165MM
- MN-92-014 Circular saw 1200 W /185 mm
- MN-92-015 Circular saw 1500 W /185 mm

Technical properties

Index	Outer diameter of the disc	Internal diameter of the disc	Reducing ring saw blade	Thickness of the saw blade	Number of teeth of the saw blade	Box	Outer	Box weight	Outer weight	EAN
	[mm]	[mm]	[mm]	[mm]	[teeth]	[pcs]	[pcs]	[kg]	[kg]	
MN-65-805	130	20	16	1.4	24	6	60	0.94	9.4	5906757137554
MN-65-810	140	20	16; 12,7	1.4	24	6	60	1.07	10.7	5906757137561
MN-65-815	152	20	16	1.4	30	6	60	1.38	13.8	5906757137578
MN-65-819	160	20	16	1.4	24	6	60	1.45	14.5	5906757157088
MN-65-820	160	20	16	1.4	36	6	60	1.50	15.0	5906757137585
MN-65-825	170	30	20; 16	1.4	36	6	36	1.68	10.1	5906757137592
MN-65-827	180	30	20; 16	1.4	24	6	36	1.91	11.4	5906757157095
MN-65-830	184	30	20; 16	1.4	40	6	36	2.0	12.2	5906757137608
MN-65-835	190	30	20; 16	2	40	6	36	2.0	11.8	5906757137615
MN-65-839	200	30	20; 16	3	24	6	24	2.6	10.2	5906757157118
MN-65-840	200	30	20; 16	3	40	6	24	2.4	9.5	5906757137622
MN-65-845	203	30	20; 16	3	30	6	24	2.6	10.4	5906757137639
MN-65-848	250	30	20; 16	3	24	6	12	4.9	9.8	5906757157125
MN-65-850	250	30	20; 16	3	60	6	12	5.0	10.0	5906757137646
MN-65-855	300	30	20; 16	4	40	1	12	1.23	14.7	5906757157149
MN-65-860	350	30	20; 16	4	40	1	6	1.80	10.8	5906757157156
MN-65-862	350	30	20; 16	4	60	1	6	1.85	11.1	5906757274914
MN-65-866	400	30	20; 16	4	48	1	6	2.7	16.2	5906757157163
MN-65-867	400	30	20; 16	4	60	1	6	2.6	15.8	5906757274921
MN-65-870	450	30	20; 16	4	60	1	5	3.3	16.3	5906757274938

Warnings



- Always use eye protection
- Always use gloves
- Always use ear protection
- Always use dust mask