

R-SL-DEK-SPEC Resin Roof Sealant

Possibility of application underwater and during heavy rainfall

Product information



Applications

- Sealing of roof flashings, terraces, chimneys and hatches.
- Sealing of break-through points in roofs and terraces.
- Repairs for bitumen roof coverings.
- Sealing skylights and roof windows.
- Connections of trapezoidal and corrugated sheets, asbestos-cement and bituminous sheets.
- Connections between foundation and basement wall components, as well as filling expansion joints of roofs and terraces.

Features and benefits

- For the majority of seals in roofing applications.
- Adheres to substrates including: sheet metal, bitumen, concrete, stone, metal, wood, glass and most plastics.
- Can be painted after hardening.
- Resistant to weathering, temperature extremes and UV radiation.
- Permanently plastic - resistant for cracking

Base materials

Approved for use in:

- Glass
- Metal Sheet & Profiles
- Stainless Steel
- Ceramics
- Concrete
- High-Density Natural Stone
- Wood
- Aluminium
- Bituminous substrates
- Tile

Installation guide

1. Clean up the gap. Surface, that the paste will be applied on, should be dry, clean, free of dust, dirt, grease, oil, rust, remains of old sealant and other substances that might lower the cohesion.
2. In case of absorptive substrates, the priming is suggested. The test of adhesion prior application is also recommended.
3. The product can be applied underwater or during intensive rainfall.
4. Applied product may be smoothed with a spatula or similar tool. Moisten the spatula first in water solution of soap.
5. After completing the application, wipe tools with a paper towel and clean with solvent.

Technical Data

Parameter		Value	Methods
Application temperature	[°C]	+5 ÷ +40	
Coverage	-	18 linear meters of 4x4 mm joint per one 300 ml cartridge	
Thermal resistance (upon hardening)	-	-20 ÷ +90	
Pretreatment time	[h]	1	
Hardening system	-	one-component-solvent evaporation	
Hardening type	-	solvent evaporation	
Density	[kg/dm ³]	1,08	
Packaging	-	300 ml cartridge	
R-SL-DEK-01-SPEC			
Colour	-	colourless	
R-SL-DEK-04-SPEC			
Colour	-	brown	
R-SL-DEK-06-SPEC			
Colour	-	brick red	
R-SL-DEK-07-SPEC			
Colour	-	graphite	

Parameter		Value
Storage temperature	[°C]	+5 ÷ +35
Storage	[month]	18
	-	In originally closed containers, in cool and dry places.

Product commercial data

Product Code	Colour	Quantity [pcs]			Weight [kg]			Bar Codes
		Box	Outer	Pallet	Box	Outer	Pallet	
R-SL-DEK-01-SPEC	colourless	15	15	1260	5.8	5.8	513.8	5906675277608
R-SL-DEK-04-SPEC	brown	15	15	1260	5.9	5.9	527.4	5906675277615
R-SL-DEK-06-SPEC	brick red	15	15	1260	6.0	6.0	532.1	5906675313603
R-SL-DEK-07-SPEC	graphite	15	15	1260	5.9	5.9	527.4	5906675313610