

R-SL-FIX-SBS Mounting Adhesive SBS

Mounting Adhesive SBS - universal with very good adhesion. Recommended for mounting and finishing works.

Product information



Applications

- Installation of panels, profiles, moldings and wall skirtings.
- Bonding of window sills, plafonds, stone and ceramic tiles.
- Fixing of doorsteps, stairs and cornices.
- Should not be applied on styrofoam.

Features and benefits

- Very good adhesion to wood, MDF, HDF, concrete, plaster, brick, metal, glass, hard PVC, and the most common materials in the building industry
- High bonding strength
- Remains flexible after hardening
- Ideal for renovations and finishing works
- [English]: Do stosowania wewnątrz pomieszczeń
- Fast curing and effective penetration of the substrate

Base materials

Approved for use in:

- Concrete
- Masonry
- Wood
- Plasterboard
- Oriented Strand Board
- High-Density Natural Stone
- PVC Profile
- Glass

Installation guide

1. The surface, that adhesive will be applied on, should be clean, free of dust, grease, rust, remains of old seal and other substances that might weaken the cohesion.
2. Cut the tip of the cartridge, leaving part of the thread. Screw the applicator on to the thread, then cut at the required angle to give an aperture width suited to the joint.
3. Place the cartridge in the extruding gun and apply the adhesive with manual or pneumatic gun.
4. Apply drops or strips of adhesive on the glued surface and spread thoroughly. Join the surfaces and disconnect. Wait 5 minutes. stick together again and press firmly.
5. The joint achieves its ultimate strength in 1-7 days, dependingly on the type of material, layer thickness and conditions. The placement of the glued piece can be amended only by move it without disconnecting.
6. After completing the application, wipe tools with a paper towel and clean with solvent.

Technical Data

Parameter		Value	Methods
Application temperature	[°C]	+10 ÷ +35	
Coverage	-	18 linear meters of 4x4 mm joint per one 300 ml cartridge	
Thermal resistance (upon hardening)	[°C]	-18 ÷ +60	
Pretreatment time	[min]	2	
Curing time	[mm/24h]	2	RH 55%
Hardening type	-	solvent evaporation	
Density	[g/cm ³]	1,56	
Packaging	-	300 ml cartridge	
R-SL-FIX-08-SBS			
Colour	-	beige	

Parameter		Value
Storage temperature	[°C]	+10 ÷ +35
Storage	[month]	12
	-	In originally closed containers, in cool and dry places.

Product commercial data

Product Code	Colour	Quantity [pcs]			Weight [kg]			Bar Codes
		Box	Outer	Pallet	Box	Outer	Pallet	
R-SL-FIX-08-SBS	beige	15	15	1260	7.8	7.8	687.1	5906675313641