

# R-SL-MA-FAST Light Fast Acrylic

Acrylic dispersion sealant

## Product information



### Applications

- Filling cracks in walls and ceilings
- Fast repair defects in cracks - can be sanded and painted 20 min after application
- Grouting connections joints of drywall boards
- Covering screw heads & bolts
- Filling joints during installation of partition walls and suspended ceilings

### Features and benefits

- Perfect adhesion to the most building materials (including porous)
- No shrinkage - can be applied with a thin layer without the risk of shrinkage and cracking
- Easy and fast application and work- filling, smoothing and polishing seals
- No need to use Anti-Scratch Tape
- Dust-free grinding
- For interior use

### Base materials

#### Approved for use in:

- Concrete
- Masonry
- Wood
- Plasterboard
- Oriented Strand Board
- High-Density Natural Stone
- Plaster

## Installation guide



1. Clean up the gap. Surface, that the acrylic will be applied on, should be clean, free of dust, dirt, grease, oil, rust, remains of old sealant and other substances that might lower the cohesion.
2. In case of absorptive substrates, the priming is suggested. The test of adhesion prior application is also recommended.
3. Prior to application, protect edges with masking tape
4. Cut the tip of the cartridge, leaving part of the thread. Screw the applicator on to the thread, then cut at the required angle to give an aperture width suited to the joint.
5. Use manual or pneumatic gun applicator.
6. The applied acrylic can be smoothed with a spatula.
7. After completing the application, wipe tools with a paper towel and wash with water.
8. Fully dried product should be secured with plaster, paint etc.

## Technical Data

Parameter		Value	Methods
Application temperature	[°C]	+5 ÷ +35	
Coverage	-	18 linear meters of 4x4 mm joint per one 300 ml cartridge	
Thermal resistance (upon hardening)	[°C]	-20 ÷ +75	
Pretreatment time	[min]	5	
Drying time	[min]	20	
Hardening system	-	one-component-water evaporation	
Density	[kg/dm <sup>3</sup> ]	0,7	
<b>R-SL-MA-02-FAST</b>			
Packaging	-	300 ml cartridge	
Colour	-	white	

Parameter		Value
Storage temperature	[°C]	+5 ÷ +30
Storage	[month]	18
	-	In originally closed containers, in cool and dry places.

## Product commercial data

Product Code	Colour	Quantity [pcs]			Weight [kg]			Bar Codes
		Box	Outer	Pallet	Box	Outer	Pallet	
R-SL-MA-02-FAST	white	15	15	1260	5.1	5.1	455.9	5906675313658