



**MN-94-009 Heat gun 2000W, 2-stage, 6-step adjustment****Universal 2000 W heat gun with 6-step temperature adjustment****Certificates (icon):****Features & benefits**

- A 2000 W heating element ensures quick start-up, efficient operation and high maximum temperature
- Two stages: the first stage enables temperature adjustment in the range of 50-350 deg C (with 50 deg C increments), the second stage enables temperature adjustment in the range of 100-600 deg C (with 100 deg C increments).
- 6-step adjustment of the parameters of the tool's operation presented via LED indicators allows appropriate temperature to be set for the work being performed
- Constant airflow of 550 liters/minute at both stages ensures strong airstream and therefore efficient operation
- The design of the heat gun allows it to be placed vertically as a stationary equipment and the material to be operated using both hands
- Two component rubber handle guarantees a secure and comfortable grip and makes the operation more ergonomic
- Hand guard prevents accidental burning due to the user touching the material being worked on
- Light, strong body of the heat gun means greater durability and reduced fatigue during work
- Rich set of accessories: 4 nozzles, a putty knife and a scraper, allowing a wide variety of works to be carried out without the need to buy any additional tools
- Carrying case enables easy transport of and provides convenient storage space for the tool and all its accessories
- **Red Plug Service** guarantees quick repair of a broken tool though free courier shipment from and to the customer

**Applications**

- Intended for the removal of paint and other paint coatings
- Intended for soft soldering of steel, copper and brass components
- Intended for forming and welding plastics
- Intended for veneering furniture and many other applications such as defrosting, drying or firing up the grill

## Equipment

- 4 interchangeable tools/attachments/nozzles
- Putty knife
- Triangular scraper
- Carrying case

## Users

- Varnishers
- Painters
- Carpenters
- Plumbers
- DIY enthusiasts

## Technical properties

Index	Power	Box	Outer	Box weight	Outer weight	EAN
	[W]	[pcs]	[pcs]	[kg]	[kg]	
<b>MN-94-009</b>	2000	1	5	2.1	10.7	5906675099163

<b>power</b>	<b>2000 W</b>
temperature: level I	<b>50-350 °C</b>
temperature: level II	<b>100-600 °C</b>
efficiency	<b>550 L/min</b>
cord length	<b>3 m</b>

## Warnings



- Read user manual
- Always use eye protection
- Always use gloves
- Always use dust mask
- USER'S MANUAL. Always follow safety instructions contained in the user's manual and applicable health and safety at work regulations. The failure to comply with warnings and recommendations contained therein may result in electric shock, fire, serious injuries and even death. Read and understand the user's manual carefully and keep it for future reference