

R-RAWL-WW90CH Gas powered framing nailer

High performance gas powered framing nailer for timber framing and roofing applications



Certificate



Product information

Features and benefits

- Nail range from 50mm to 90mm for wide range of applications
- Removable no mark nose for protecting the timber surface. Especially important when securing timber cladding or facades
- Sequential firing mode for operators safety and fixing precision
- Rear loading magazine with a capacity of 60 nails. Quick and simple to load thanks to one hand operation feeder spring. A safety clip at the rear prevents the nails from falling out and ensures safe reloading
- Tool free depth adjustment. The operator can easily adjust the depth that the nail is driven into timber to produce a precise fixing

Applications

- Timber frame stud work in timber framing industry
- Installation of battens and sheathing in roof construction
- Manufacturing of timber standardised structure like Timber frame houses or roof elements

Corresponding products


- R-DPK paper collated nails with fuel cells
- R-DRK paper collated nails with fuel cells
- R-DPG paper collated nails with fuel cells

Base materials

- Timber
- Chipboard
- Plywood
- Wood

Set includes

- R-RAWL-WW90CH Gas powered nailer
- 2 batteries
- Charger base
- AC power supply cable
- Operating and Safety manual



Product commercial data

Index	Fastener length range	Fastener type	Substrate	Dimensions	Fuel cell type	WEIGHT	Magazine capacity	Battery charge	Shots per charge	Noise level	Box weight	Outer weight	EAN
	[mm]			[mm]		[kg]	[nail]			[dB]			
R-RAWL-WW90CH	50 - 90	Clipped head nail	Timber	367 x 372 x 108	GP1	3.4	60	2	4000	94	8.61	17.23	590667522240