

R-RAWL-PMC-38 Pneumatic joist hanger nailer

Compact pneumatic positive placement nailer for quick installation of metalconnectors



Certificate



Product information

Features and benefits

- Compatible with all 38 twist shank nails present on the market for freedom of choice
- Nose tip with probe mechanism locates the tool in the pre drilled hole for a precise and quick fixing. Easy to operate even in areas with limited access
- Extremely lightweight and manouverable which is an advantage when operating in areas with limited access
- Reduced risk of hand injury thanks to low recoil and low weight
- Magazine capacity 30 nails enables to limit the time needed for reloading
- Rotary belt hook provides safety and comfort during daily operation
- 360 degree rotary air connector allows for great accessibility in tight spaces

Applications

- Installation of all types of metal connectors
- Installation of truss supports and angled joints
- Installation of perforated steel tapes

Corresponding products

- R-DPCG paper collated nails
- R-RAWL-C24 Oil lubricated compressor
- R-RAWL-C50 Oil lubricated compressor

Base materials

- Timber
- Wood

Set includes

- R-RAWL-PMC-38 Pneumatic positive placement nailer
- Spare gasket set
- Operating and Safety manual
- Safety glasses and ear plugs
- Case



Product commercial data

Index	Power source	Magazine type	Magazine capacity	Magazine angle	WEIGHT	Fastener diameter range	Fastener length range	Noise level	Maximum pressure	Operating pressure	Box weight	Outer weight	EAN
			[nail]	[degree]	[kg]	[mm]	[mm]	[dB]	[bar]	[bar]	kg	kg	
R-RAWL-PMC-38	Pneumatic	Strip	29	34	2.5	3.3 - 4.1	38	94	8	5-7	4.64	23.19	5906675251998