

RT-BIT-PZ Pozidriv atsuktuvo antgaliai

„Pozidriv“ atsuktuvų antgaliai su preciziškai frezuota galvute



Informacija apie gaminį

Savybės ir privalumai

- [Lithuanian]: Specially heat treated in the hardening process to increase the hardness of the tip to 60 HRC
- [Lithuanian]: Precision milled head tip allows for precise fitting into the screw socket
- [Lithuanian]: The special shape of the tip increases its resistance to twisting under the so-called torsion effect
- [Lithuanian]: Anti-corrosion coating, blue colour, prevents rust

Naudojimas

- Sukimas Pozidriv varžtų plataus pasirinkimo nuo medienos ir šviesos prietaisų prisukimų darbams

Suderinami gaminiai

- UNO® Universali smeigė su varžtu
- 4ALL Universali smeigė su varžtu
- FX-N-C Įkalama nailoninė smeigė su cilindrine mova



Logistikos duomenys

Rodyklė	Dydis	Ilgis	Kiekis	Dėžės svoris	Išorinis svoris	EAN
		[mm]	[vnt]	kg	kg	
RT-BIT-PZ1/25	PZ1	25	20	0.09	0.87	5906675034973
RT-BIT-PZ2/25	PZ2	25	20	0.11	1.09	5906675034980
RT-BIT-PZ2/50	PZ2	50	10	0.06	0.57	5906675035048
RT-BIT-PZ3/25	PZ3	25	20	0.11	1.11	5906675038018
RT-BIT-PZ1X3	PZ1	25	3	1.06	10.56	5906675072319
RT-BIT-PZ2X3	PZ2	25	3	1.15	11.52	5906675072333
RT-BIT-PZ3X3	PH3	25	3	0.03	1.25	5906675072340
RT-BIT-PZ123	PZ1 PZ2 PZ3	25	3	1.20	12.00	5906675072401