

RT-BIT-TORX T tipo atsuktuvo antgaliai

T tipo atsuktuvo antgaliai su preciziškai frezuota galvute



Informacija apie gaminį

Savybės ir privalumai

- [Lithuanian]: Precision milled head tip allows for precise fitting into the screw socket
- [Lithuanian]: Special steel S2 affects the life of the product
- [Lithuanian]: Specially heat treated in the hardening process to increase the hardness of the tip to 60 HRC
- [Lithuanian]: The special shape of the tip increases its resistance to twisting under the so-called torsion effect
- [Lithuanian]: Anti-corrosion coating, blue colour, prevents rust

Naudojimas

- T tipo varžtų sukimas medienai, metalui ir betonui

Suderinami gaminiai

- R-DSX-A2 nerūdijančiojo plieno varžtai, skirti dangai
- R-FF1-N-L-DT RĖMINĖ SMEIGĖ SU CINKUOTU VARŽTU IR KŪGINE GALVUTE, PADENGTA „DELTA TONE“



Logistikos duomenys

Rodyklė	Dydis	Ilgis	Kiekis	Dėžės svoris	Išorinis svoris	EAN
		[mm]	[vnt]	kg	kg	
RT-BIT-TORX10/25	T10	25	20	0.08	0.75	5906675335858
RT-BIT-TORX10X3	T10	25	3	0.02	0.24	5906675406176
RT-BIT-TORX15/25	T15	25	20	0.08	0.80	5906675335865
RT-BIT-TORX15X3	T15	25	3	0.02	0.24	5906675406183
RT-BIT-TORX20/25	T20	25	20	0.30	3.00	5906675335872
RT-BIT-TORX20X3	T20	25	3	1.15	11.52	5906675406190
RT-BIT-TORX25/25	T25	25	20	0.09	0.92	5906675035000
RT-BIT-TORX25X3	T25	25	3	1.10	11.04	5906675072357
RT-BIT-TORX30/25	T30	25	20	0.12	1.15	5906675035017
RT-BIT-TORX30X3	T30	25	3	1.20	12.00	5906675072364
RT-BIT-TORX40/25	T40	25	20	0.13	1.31	5906675035024
RT-BIT-TORX40X3	T40	25	3	1.34	13.44	5906675072371
RT-BIT-TORX45X3	T45	25	3	0.03	12.00	5906675428338
RT-BIT-TORX50/25	T50	25	20	0.30	3.00	5906675335889
RT-BIT-TORX50X3	T50	25	3	0.02	0.24	5906675406206
RT-BIT-T253040	T25 T30 T40	25	3	1.15	11.52	5906675072418